MPPT Solar Charge Controller

PC1800F SERIES (60A/80A/100A)

MPPT (Maximum Power Point Tracking)Solar Charge Controller offer an efficient, safe, multi-stage recharging process that prolongs battery life and assures peak performance from a solar array. Each Charge Controller allows customized battery recharging.

Max charging current 60A / 80A / 100A

Fan cooling

Multi protection

Battery smart charge design

Battery DC voltage 12V/24V/48V(Auto detection) 36V(Setting)

Peak conversion efficiency : 98% (MPPT Efficiency 99%)

Charging set points Absorption stage Float stage

Appearance

(60A / 80A)



(100A)

PRODUCT FEATURES

SMART & INTELLIGENT FEATURES

- LCD display , easy to operate on LCD screen
- Multi stage charging (3-stage charging , parallel charging and equalized charging function)
- BTS - Battery remote temperature sensor terminal
- Enable to charge Li-thium, Gel , lead-acid battery
- With RS485 & USB communication port
- Protection: PV array short circuit, PV reverse polarity, Battery reverse polarity, Over charging, Output short circuit

RS485/USB Communication

The default communication of the controller is RS485 port.You can use supplied cable to connect RS485,USB port of controller to PC.It can be used for monitoring or upgrade the firmware in short distance.

Equalize stage charging function

Equalization function reverses the buildup of negative chemical effects like stratification,a condition where acid concentration is greater at the bottom of the battery than at the top.Equalization also helps to remove sulfate crystals that might have built up on the plates.



Battery reverse protection

TThere's a battery reverse protection function in the board, then the controller will be perfectly protected even installer or user connect the battery in reverse pole accidentally

PRODUCT DETAILS

MUST HELP YOU CONTROL EVERY DETAIL

Details reflect quality


POWER CHARGING FAULT WARNING WIRING FAULT
ON/MENU
UP
DOWN
ENTER
LCD display
Power ON/Charging indicator
Fault and warning indicator
Wiring fault indicator
Operation button
Battery temoerature sensor terminal
USB
RS485 communication port

SOLAR SYSTEM CONNECTION

INVERTER + SOLAR CHARGE CONTROLLER + BATTERY + SOLAR PANELS + GRID + APPLICATION LOADS



PC1800F solar inverter system， it can work with inverter , battery and solar panel , as a complete solar system and back up power for normal home power demands , which take use of sunshine free and save lots of electricity bill for you . This kind of solar inverter systems are widely used in home ,farm ,school,shops etc .

PRODUCT PARAMETERS

MAKE SURE EACH PARAMETER IS TRUE

Learn more about the product

MODEL		PC18-6015F		PC18-8015F		PC18-10015F
Nominal Battery System Voltage		12V/24V/48VDC (Auto detection); 36V (Setting)				
CONTROLLER INPUT	Battery Voltage	12V	24V	36V	48V	48V
	Maximum Solar Input Voltage	100V		145V		
	PV Array MPPT Voltage Range	15~95V	30~130V	45~130V	60~130V	60~130V
	Maximum Input Power	12Volt-940W 24Volt-1880W 36Volt-2820W 48Volt-3760W		12Volt-1250W 24Volt-2500W 36Volt-3750W 48Volt-5000W		12Volt-1550W 24Volt-3100W 36Volt-4650W 48Volt-6200W
BATTERY	Charging Set Points	Absorption Stage			Float Stage	
	Flooded Battery	14.2V/28.4V/42.6V/56.8V			13.7V/27.4V/41.1V/54.8V	
	AGM (Default)	14.4V/28.8V/43.2V/57.6V			13.7V/27.4V/41.1V/54.8V	
	Over-charging Voltage	15.5V/30.0V/45.0V/60.0V				
	Over-charging Comeback Voltage	14.5V/29.5V/44.5V/59.0V				
	Battery Defect Voltage	10.0V/17.0V/25.5V/34.0V				
	Temperature Compensation Coneficient	-5mv / °C /cell (25°C vef)				
	Peak Conversion Efficiency	98% (MPPT Efficiency 99%)				
	Max Charging Current	60amps continuous @ 40°C ambient		80amps continuous @ 40°C ambient		100amps continuous @ 40°C ambient
GENERAL SPECIFICATION	Radiating Mode	Fan cooling				
DISPLAY & PROTECTION	Protections	Solar high voltage disconnect Solar high voltage reconnect Battery high voltage disconnect Battery high voltage reconnect High temperature disconnect High temperature reconnect				
MECHANICAL SPECIFICATIONS	Mounting	Wall mount				
	Machine Dimension (W*H*D)	152*85*294 mm (per pcs)				175*82.9*257.1
	G.W (kg)	3kg/pcs				
	Package Dimension (W*H*D)	625*366*232 mm (4pcs / Carton)				/
	Gross Weight (kg)	14kg				
OTHER	Environmental Rating	Indoor				
	Operation Temperature Range	-10~55°C				
	Ambient Humidity	0~90% relative humidity (non-condensing)				
	Altiude	≤3000m				

Size



(60A / 80A)



(100A)

Package

User Manual

Warranty Card

Communication Cable


BTS Cable

COLOR BOX DIMENSION		
COLOR BOX SIZE : 359*149*217MM (1PC)	CARTON SIZE : 625*366*232MM (4PCS/CARTON)	
LOADING		
20GP	40GP	40HQ
3000pcs	6000pcs	7200pcs

Packaging

PRACTICAL APPLICATION

APPLICABLE PLACE



The solar charge controller is an automatic control device , it can be used in all solar power systems to control solar panel array to charge batteries . Solar Inverter System Connection: Power Inverter + Solar Charge Controller + Battery + Solar Panels + Grid + Applicaiton Loads

PROJECT REFERENCE

PROFESSIONAL CERTIFICATION

CE FCC ROHS ISO9001

High quality and high standard

CERTIFICATE

CERTIFICATE

TEST REPORT

Have quality inspection to use with confidence



MUST SHENZHEN MUST ENERGY TECHNOLOGY CO.,LTD.