

SUNNY HIGHPOWER PEAK3

125-US / 150-US / 165-US / 172-US



SHP 125-US-21 / SHP 150-US-21 / SHP 165-US-21 / SHP 172-US-21



25 YEAR
DESIGN LIFE



SMA
Smart Connected



Cost effective

- Modular architecture reduces BOS and maximizes system uptime
- Compact design and high power density maximize transportation and logistical efficiency

Maximum flexibility

- Scalable 1,500 VDC building block with best-in-class performance
- Flexible architecture creates scalability while maximizing land usage

Simple install, commissioning

- Ergonomic handling and simple connections enable quick installation
- Centralized commissioning and control with SMA Data Manager

Highly innovative

- SMA Smart Connected reduces O&M costs and simplifies field-service
- Powered by award winning ennexOS cross sector energy management platform

SUNNY HIGHPOWER PEAK3

125-US / 150-US / 165-US / 172-US

A superior modular solution for large-scale power plants

The PEAK3 1,500 VDC inverter offers high power density in a modular architecture that achieves a cost-optimized solution for large-scale PV integrators. With fast, simple installation and commissioning, the Sunny Highpower PEAK3 is accelerating the path to energization. SMA has also brought its field-proven Smart Connected technology to the PEAK3, which simplifies O&M and contributes to lower lifetime service costs. The PEAK3 power plant solution is powered by the ennexOS cross sector energy management platform, 2018 winner of the Intersolar smarter E AWARD.

Technical Data	Sunny Highpower PEAK3 125-US	Sunny Highpower PEAK3 150-US	Sunny Highpower PEAK3 165-US	Sunny Highpower PEAK3 172-US
Input (DC)				
Maximum array power ¹⁾	250 kWp	300 kWp	330 kWp	344 kWp
Maximum system voltage	1500 Vdc			
Rated MPP voltage range	705 V ... 1450 V	880 V ... 1450 V	924 V ... 1450 V	968 V ... 1450 V
MPPT operating voltage range	684 V ... 1500 V	855 V ... 1500 V	898 V ... 1500 V	941 V ... 1500 V
MPP trackers	1			
Maximum operating input current	180 A			
Maximum input short-circuit current	325 A			
Output (AC)				
Nominal AC power	125 kW	150 kW	165 kW	172 kW
Maximum apparent power	125 kVA	150 kVA	165 kVA	172 kVA
Output phases / line connections	3 / 3-PE			
Nominal AC voltage	480 V	600 V	630 V	660 V
Compatible transformer winding configuration	Wye-grounded			
Maximum output current	151 A			
Rated grid frequency	60 Hz			
Grid frequency / range	50 Hz, 60 Hz / -6 Hz ... +6 Hz			
Power factor at rated power / adjustable displacement	1 / 0.8 leading ... 0.8 lagging			
Harmonics (THD)	<3%			
Efficiency				
CEC efficiency	98.5 %	99.0 %	99.0 %	99.0 %
Protection and safety features				
Ground fault monitoring: Riso / Differential current	● / ●			
DC reverse polarity protection	●			
AC short circuit protection	●			
Monitored surge protection (Type 2): DC / AC	● / ●			
Protection class / overvoltage category (as per UL 840)	I / IV			
General data				
Device dimensions (W / H / D)	770 / 830 / 462 mm (30.3 / 32.7 / 18.2 in)			
Device weight	99 kg (218 lbs)			
Operating temperature range	-25 °C ... +60 °C (-13 °F ... +140 °F)			
Storage temperature range	-40 °C ... +70 °C (-40 °F ... +158 °F)			
Audible noise emission (full power @ 1m and 25 °C)	< 69 dB(A)			
Internal consumption at night	< 5 W			
Topology	Transformerless			
Cooling concept	OptiCool (forced convection, variable speed fans)			
Enclosure protection rating	Type 4X			
Maximum permissible relative humidity (non-condensing)	100%			
Additional information				
Mounting	Rack mount			
DC connection	Terminal lug (up to 600 kcmil CU/AL)			
AC connection	Screw terminal (up to 300 kcmil CU/AL)			
LED indicators (Status/Fault/Communication)	●			
SMA Speedwire (Ethernet network interface)	● (2 x RJ45 ports)			
Data protocols: SMA Modbus / SunSpec Modbus	● / ●			
Integrated Plant Control / Q on Demand 24/7	● / ●			
Off-grid capable / SMA Hybrid Controller compatible	- / ●			
Monitoring				
SMA Sunny Portal (monitoring portal)	No cost for the lifetime of the system			
SMA Smart Connected (monitoring and remote O&M service)	No cost on inverters under warranty			
Supported protocols for outbound data	SMA external API, Modbus, FTP			
Certifications				
Certifications and approvals (pending)	UL 62109, UL 1998, CAN/CSA-C22.2 No.62109			
Manufacturer's Declaration of Design Life	25 years			
FCC compliance	FCC Part 15, Class A			
Grid interconnection standards	IEEE 1547:2018, UL 1741-SA - CA Rule 21, HECO Rule 14H, UL1741SB			
Advanced grid support capabilities	L/HFRT, L/HVRT, Volt-VAr, Volt-Watt, Frequency-Watt, Ramp Rate Control, Fixed Power Factor			
Warranty				
Standard	5 years			
Optional extensions	10 / 15 / 20 / 25 years			
1) Higher DC array power permitted via site inverter load modeling in SMA Sunny Design				
Type designation	SHP 125-US-21	SHP 150-US-21	SHP 165-US-21	SHP 172-US-21
● Standard features ○ Optional features – Not available				

SHP-US-Dee-22 - Changes to products and services, including those resulting from country-specific requirements, as well as deviations from technical data are subject to change at any time without notice. SMA assumes no liability for typographical or other errors. Please visit www.SMA.Solar.com for the latest information.